

PRODUCT INFORMATION

ECOSE® GL-1 GEAR OIL

ECOSE® GL-1 Gear Oil is a quality multi-purpose, multi-viscosity grade gear lubricant designed for gear boxes, manual transmissions and other automotive, agricultural and industrial applications where a GL-1 quality lubricant is specified, and EP properties are not required.

ECOSE® GL-1 Gear Oil is made from highly-refined paraffinic base stocks and has excellent seal compatibility and good low temperature performance.

FEATURES AND APPLICATIONS:

- Where API GL-1 gear oils are recommended
- Non-foaming
- Where extreme pressure (EP) performance is not required
- In certain older model heavy-duty truck rear axles
- In certain older model automobile rear axles and manual transmissions
- Vintage farm tractors and equipment
- Straight mineral oil is specified by manufacturer

Typical Properties

SAE Grade	Test Method	80W-90
Product Code		532100
Viscosity, cSt @ 40°C	ASTM D-2161	135
Viscosity, cSt @ 100°C	ASTM D-2161	14.0
Viscosity Index		100
Brookfield Viscosity, cP	ASTM D-2983	120,000 (-26°C)
Pour Point, °F	ASTM D-97	-15
Flash Point, COC, °F	ASTM D-92	500
Specific Gravity @ 60°F		0.878

*Do not use in hypoid gear sets or other automotive applications requiring an extreme pressure lubricant.

AVAILABILITY:

ECOSE® GL-1 Gear Oil is available throughout Nu-Tier Brand’s marketing area. Your Nu-Tier representative can provide specific information. Need additional information? Call Nu-Tier Brands @ 1-877-771-LUBE (5823) or visit Nu-tierbrands.com.