



Gulf BioTribe Hydraulic Fluid

SDS - Safety Data Sheet

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Gulf BioTribe Hydraulic Fluid
Other means of identification: Biodegradable, Zinc Free Hydraulic Fluid
SDS Number: 334320
CAS Number: Blend
CHEMTREC: EMERGENCY CONTACT 1-800-424-9300

Supplier:
Nu-Tier Brands, Inc., East Greenbush, NY
Under License from Gulf Oil LP
TECHNICAL CONTACT NUMBER: 1-800-566-4853
www.gulflubricants.net

2. HAZARDS IDENTIFICATION

Classified Hazards This material is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.	Other Hazards None Known
---	------------------------------------

Label Elements

No classified hazards

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS	Concentration
Vegetable Oil / Additives	Mixture	>95%
Proprietary Additives	Mixture	<5%

4. FIRST AID MEASURES

INHALATION FIRST AID: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.

SKIN CONTACT FIRST AID: Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.

EYE CONTACT FIRST AID: Flush with water for several minutes. If effects occur, consult a physician.

INGESTION FIRST AID: Rinse mouth with water. If symptoms develop, obtain medical attention.

5. FIREFIGHTING MEASURES

Basic Firefighting Procedures

FIRE FIGHTING NFPA Rating: **Health – 0, Fire – 1, Reactivity – 0** PROCEDURES: Hazard Rating: Least – 0 Slight - 1 High - 3 Extreme – 4 EXTINGUISHING MEDIA: Carbon dioxide, regular foam or dry chemical CONDITIONS OF FLAMMABILITY: Intense heat, sparks or flame

Fire Fighting Instructions:

This material will burn although it is not easily ignited. See Section 7 for proper handling and storage. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus. Decomposition



Gulf BioTribe Hydraulic Fluid

SDS - Safety Data Sheet

and combustion products may be toxic. Heated containers may rupture, explode or be thrown into the air. Vapors are heavier than air and may travel great distances to ignition sources and flash back or explode. Not sensitive to mechanical impact or static discharge.

Combustion Products:

Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion.

6. ACCIDENTAL RELEASE MEASURES

Refer to Section 8: Exposure Control and Personal Protection

Protective Measures: Eliminate all sources of ignition in vicinity of spilled material.

Spill Management: Remove all ignition sources. Stop leak if you can do it without risk. Ventilate area and avoid breathing vapor or mist. For large spills, dike far ahead of liquid spill for later disposal. Contain away from surface waters and sewers. Absorb with compatible absorbent material and shovel into closable container for disposal. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

Notification Any spill or release to navigable water that causes a visible sheen upon the water must be reported immediately to the National Response Center (800/424-8802), as required by U.S. federal law.

7. HANDLING AND STORAGE

Refer to Section 8: Exposure Control and Personal Protection

Precautionary Measures:

Keep away from intense heat, sparks or flame. Avoid contact with eyes, skin, clothing or shoes. Use in well-ventilated area and avoid breathing vapor or mist.

General Handling Information:

Use good personal hygiene. Wash thoroughly with soap and water after handling and before eating, drinking or using tobacco products. Clean contaminated clothing, shoes and protective equipment before reuse. Discard contaminated clothing, shoes or protective equipment if they cannot be thoroughly cleaned.

Container Warnings:

Keep container tightly closed when not in use and during transport. Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Component: Highly refined mineral oil - TWA STEL ACGIH 5 mg/m³ 10 mg/m³ - OSHA Z-1 5 mg/m³

Engineering Controls

Provide process enclosure or local ventilation needed to maintain concentration of vapor or mist below applicable exposure limits.

Eye and Face Protection

Wear protective eyewear. Do NOT wear contact lenses. Use face shield if splashing is possible.

Skin Protection

Use Neoprene, Nitrile, PVC or equivalent gloves to prevent contact with skin. Do NOT use natural rubber or equivalent gloves.

Respiratory Protection



Gulf BioTribe Hydraulic Fluid

SDS - Safety Data Sheet

Use NIOSH/MSHA-approved respiratory protective equipment when concentration of vapor or mist exceeds applicable exposure limit. A self-contained breathing apparatus (SCBA) and full protective equipment is required for fire emergencies. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134 or in Canada with CSA Standard Z94.4-M1982.

Other Protective Equipment

Where spills and splashes are possible, wear appropriate oil-resistant boots, apron or other protective clothing. Clean water should be available in work areas for flushing the eyes and skin.

9. PHYSICAL AND CHEMICAL PROPERTIES

Note: Data represents typical values and are not intended to be specifications.

General Information:

Physical State:

Form: Clear Liquid

Color: Green

Odor: Bland

Important Health, Safety and Environment Info

Boiling Point/Range: NA

Flash Point: 392oF

Auto Ignition Temp: N/A

Lower Flammability Limit: N/A

Upper Flammability Limit: N/A

Vapor Pressure (psi @100°F): N/A

Vapor Density: NA

Freezing Point/Melting Point: N/A

Solubility (Water): Insoluble

Specific Gravity: 0.92

Evaporation Rate: N/A

Viscosity: NA

pH: 8.8

Other Information:

Volatility: N/A

Gravity, °API: NA

Note: Physical Data is typical values based on material tested, but may vary based on composition. Values should not be accepted as guaranteed for every lot or as specifications for this product.

10. STABILITY AND REACTIVITY

REACTIVITY: Not chemically reactive.

CHEMICAL STABILITY: Stable under normal ambient and anticipated conditions of use.

POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous reactions not anticipated.

CONDITIONS TO AVOID: Avoid all possible sources of ignition. Extended exposure to high temperatures can cause decomposition.

INCOMPATIBLE MATERIALS: Avoid contact with strong oxidizing agents and strong reducing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Not anticipated under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity Estimate: Base Oil: Acute oral toxicity LD50 (Rat) : >5.2 mg/L – Exposure Time: 4h, Test atmosphere: dust/mist Acute dermal toxicity LD50 (Rat) > 2000 mg/kg



Gulf BioTribe Hydraulic Fluid

SDS - Safety Data Sheet

Likely Routes of Exposure	Eyes and skin contact; inhalation of incidental mists or vapors; ingestion.
Acute Effects	Eyes: Contact may produce mild eye irritation and redness. Skin: Contact may produce mild skin irritation. No significant skin absorption hazard Inhalation (Breathing): High concentration of vapor or mist may be irritating to the respiratory tract. Ingestion (Swallowing): Low order of acute oral toxicity. May cause irritation of gastrointestinal tract, nausea and vomiting. Aspiration into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death.
Chronic Effects	Prolonged or repeated skin contact may cause drying or dermatitis. Any acute symptoms may be aggravated. Individuals with pre-existing lung or disorders may have increased susceptibility to the effects of exposure.
Symptoms	May include redness, drying, cracking of the skin, gastrointestinal and respiratory discomfort. Refer to Sections 2 and 4 for recommended actions.
Carcinogenicity	No components of this product are found to be carcinogens by NTP, IARC or OSHA.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Not expected to be harmful to aquatic organisms.
Persistence and Biodegradability	Biodegradation: Base oil component -- Expected to be inherently biodegradable.
Bioaccumulative Potential	Base oil component -- Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.
Mobility in Soil	Not Determined.

13. DISPOSAL CONSIDERATIONS

Use material for its intended purpose or recycle if possible. Oil collection services are available for used oil recycling or disposal. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations. Contact your sales representative or local environmental or health authorities for approved disposal or recycling methods.

14. TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME:	Not regulated
DOT CLASS:	Not regulated
DOT ID NUMBER:	Not regulated
TDG CLASSIFICATION:	Not regulated

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code: Not applicable

15. REGULATORY INFORMATION

SARA TITLE III: Product does not contain toxic chemicals subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372

ECPCRA 311/312 CATEGORIES:	1. Immediate (Acute) Health Effects: NO
	2. Delayed (Chronic) Health Effects: NO



Gulf BioTribe Hydraulic Fluid

SDS - Safety Data Sheet

CHEMICAL INVENTORIES:

3. Fire Hazard: NO
4. Sudden Release of Pressure Hazard: NO
5. Reactivity Hazard: NO
All components comply with the following chemical inventory requirements: DSL (Canada), TSCA (United States).

NEW JERSEY RTK CLASSIFICATION:

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 ET. seq., the product is to be identified as follows: PETROLEUM OIL (Motor oil)

16. OTHER INFORMATION

The data in this Material Safety Data Sheet relates only to the specific material designated herein.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Nu-Tier Brands, Inc. The data on this sheet are related only to the specific material designated herein. Nu-Tier Brands, Inc. assumes no legal responsibility for use or reliance upon these data.

NFPA 704 Hazard Class

Health: 0

Flammability: 1

Instability: 0



- 0 (Minimal)
- 1 (Slight)
- 2 (Moderate)
- 3 (Serious)
- 4 (Severe)

END OF MSDS