



LUBRICANTS



Product Data Sheet

Snow Plow Oil

Premium Low Pour Hydraulic Oil

High quality, high performance snowplow oil specifically engineered for extreme low temperature conditions. Formulated from state-of-the-art additive technology and premium quality base oils. It provides exceptional anti-wear performance, outstanding rust and corrosion protection, long service life, excellent oxidation stability and outstanding cold temperature performance where dielectric (insulating) oil is required. Product is dyed red for easy detection of leaks.

Features and Benefits

- Excellent anti-foam and anti-wear properties
- Outstanding low-temperature flow and pumpability
- Rust and corrosion protection for all metal components
- Anti-wear protection for pumps, motors, valves and other hydraulic components

Applications

- Industrial and mobile hydraulic systems
- Fruit picking mobile equipment
- Applications where dielectric (insulating) properties are required
- Garbage collection equipment
- Bucket trucks used for tree trimming
- Hydraulic lifts and public utility vehicles

Typical Properties

Product Code	Testing Method	334338
ISO Viscosity Grade		15
Color, Visual	Visual	RED
Viscosity, cSt @ 40°C	ASTM D-445	15.0
Viscosity, cSt @ 100°C	ASTM D-445	4.0
Viscosity Index	ASTM D-2270	170
Pour Point, °F	ASTM D-5949	-50
Flash Point, COC, °F	ASTM D-92	320
Rust Test	ASTM D-665 A&B	Pass
*Dielectric Strength	ASTM D877, KV, minimum	32

*Note: Values shown are typical values only. Always confirm with the original manufacturer's recommendation for proper equipment operating requirements.

*Note: Dielectric properties are measured at the point of manufacture (when packaged) at select Gulf manufacturing sites. A reduction in dielectric strength can be expected depending on humidity and particulate contamination. Containers should be kept tightly sealed and stored in a clean, dry environment. Dielectric performance applies to original packaged goods only.

Rev. 05/2021



1-800-566-4853



East Greenbush, NY



www.nu-tierbrands.com

