



LUBRICANTS



Product Data Sheet

No Rust® C-GP

General purpose rust-proofing oil

General purpose, soft film type rust preventative formulated with unique additives to impart excellent water displacement and fingerprint neutralizing properties. It is ideally suited to provide protection against metal corrosion and rusting under mildly corrosive conditions in covered storage or packaged shipment handling. This product's unique water displacing and fingerprint neutralizing properties make it an excellent choice as a rust preventative oil in various applications. Product should be applied to clean surfaces to provide maximum protection. Apply product by brushing, spraying, or dipping. Complete coverage is essential. Dipping is the most effective method of application, in which case excess product should be allowed to drain off.

Features and Benefits

- Ease of application
- Excellent metal wetting properties
- High flash point solvent carrier
- Excellent water displacement properties

Applications

- Steel sheeting
- Bearings
- Indoor conditions and will typically provide approximately 12 months of indoor protection
- Highly machined surfaces under relatively mild conditions of storage, shipment, or handling

Typical Properties

Product Code	Test Method	335380
Specific Gravity @ 60°F	ASTM D287	0.810
Viscosity @ 40°C, cSt		2.0
Viscosity, SUS @ 100°F	ASTM D445	32 - 36
Flash Point, COC, °F	ASTM D92	>160°F
Color	ASTM D1500	L1.5
Film Type		Transparent, oily
Humidity Cabinet, 120°F	ASTM D1748	+100 (hours)
Typical Shelf Life	Internal	3-4 years*

These properties are typical of current production, minor variations are to be expected in normal manufacturing.

* The main factor affecting the life of this product is storage conditions. Exposure to extreme temperature changes and moisture will reduce the shelf life of this product i.e., don't leave in the sun with the lid off. Best to keep Gulf No Rust C-GP sealed and unopened in its original container.

Rev. 06/21



1-800-566-4853



East Greenbush, NY



www.nu-tierbrands.com

