



Gulfcrown[®] EP Grease

SDS - Safety Data Sheet

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Gulfcrown[®] EP2 Grease
Gulfcrown[®] EP 000 Grease
Other means of identification: Industrial Grease
SDS Number: 343307, 343303
CAS Number: Blend
CHEMTREC: EMERGENCY CONTACT 1-800-424-9300
Supplier:
Nu-Tier Brands, Inc., East Greenbush, NY
Under License from Gulf Oil LP
TECHNICAL CONTACT NUMBER: 1-800-566-4853
www.gulflubricants.net

2. HAZARDS IDENTIFICATION

Classified Hazards
This material is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Other Hazards
None Known

Label Elements

No classified hazards

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS	Concentration	Carcinogen (OSHA or IARX)
Lithium 12 Hydroxystearate	7620-77-1	4-10%	No
Mineral Oil	64742-65-0	60-75%	No
Mineral Oil	64742-16-1 / 64741-56-6	15-30%	No
Zinc Alkyldithiophosphate	68649-42-3	0-2%	No
Mineral Oil	64742-52-5	5-15%	No

4. FIRST AID MEASURES

INHALATION FIRST AID: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention. In case of unconsciousness place patient stably inside position for transportation.

SKIN CONTACT FIRST AID: Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.

EYE CONTACT FIRST AID: Flush with water for several minutes. If effects occur, consult a physician.

INGESTION FIRST AID: Rinse mouth with water. If symptoms develop, obtain medical attention.

5. FIREFIGHTING MEASURES

NFPA 704 Hazard Class

Health: 1 Flammability: 1 Instability: 0



0 (Minimal)
1 (Slight)
2 (Moderate)
3 (Serious)
4 (Severe)

Flash Point Minimum: 400°F / 204°C

Extinguishing Media: Dry chemical, carbon dioxide, foam, or water spray is recommended. Water or foam may cause frothing of materials heated above 212°F/100°C. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.



Gulfcrown[®] EP Grease

SDS - Safety Data Sheet

Specific hazards arising from the chemical:

Unusual Fire & Explosion Hazards: This material may burn but will not ignite readily. If container is not properly cooled, it can rupture in the heat of a fire.

Hazardous Combustion Products: Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Oxides of sulfur, nitrogen or phosphorus may also be formed.

Special protective actions for firefighters: For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective clothing. When the potential chemical hazard is unknown, in enclosed or confined spaces, a self-contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8).

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can be done safely. Avoid spreading burning liquid with water used for cooling purposes.

See Section 9 for Flammable Property Including Flash Point

6. ACCIDENTAL RELEASE MEASURES

Contain spilled material.
Collect in suitable and properly labeled containers.
Pick up excess with inert absorbent material.
Keep away from drains and ground water.

7. HANDLING AND STORAGE

HANDLING PRECAUTIONS:

Avoid contact with eyes, skin, or clothing.
Keep away from sources of ignition.
Handle with care and avoid spillage on the floor (slippage).

STORAGE REQUIREMENTS:

Keep away from sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

PERSONAL PROTECTIVE EQUIPMENT:

Use of tightly sealed goggles and impermeable and resistant gloves are recommended.

GENERAL PROTECTIVE AND HYGIENIC MEASURES:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.

BREATHING EQUIPMENT:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.



Chemical Name	ACGIH	OSHA	Other
Distillates, petroleum, solvent-dewaxed heavy paraffinic (50-100%)	TLV: Long-term value: 5mg/m ³	PEL: Long-term value: 5mg/m ³	



Gulfcrown[®] EP Grease

SDS - Safety Data Sheet

Asphaltic Resin (20-<25%)	TLV: Short-term value: 10mg/m ³ Long-term value: 5mg/m ³	PEL: Long-term value: 5mg/m ³ REL: Short-term value: 10mg/m ³	
Distillates, petroleum, hydrotreated heavy naphthenic (2.5 - <10%)	TLV: Short-term value: 10 mg/m ³ Long-term value: 5mg/m ³	PEL: Long-term value: 5mg/m ³	
Ingredients with biological limit values: Asphaltic Resin (20-<25%)		BEI: Medium: urine Time: end of shift at end of workweek Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)	

9. PHYSICAL AND CHEMICAL PROPERTIES

Note: Data represents typical values and are not intended to be specifications.

Physical State:	Semi-Solid
Odor:	Petroleum-like
Melting Point:	Not determined
Boiling Point:	370°C (698°F)
Ignition Temp:	No data available
Auto igniting:	Product is not self-igniting
Danger of explosion:	Product does not present an explosion hazard
Density @ 20°C (68°F):	0.90785 g/cm ³ (7.576 lbs./ gal)
Solubility in water:	Not miscible or difficult to mix
Viscosity:	Dynamic-Not determined; Kinematic-Not determined
Flash Point:	>400°F / >204°C
VOC, % wt.:	1 (ASTM D-972)
Other information:	No further relevant information available

10. STABILITY AND REACTIVITY

REACTIVITY: Not chemically reactive.
CHEMICAL STABILITY: Stable under normal ambient and anticipated conditions of use.
POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous reactions not anticipated.
CONDITIONS TO AVOID: No further relevant information available.
THERMAL DECOMPOSITION/CONDITIONS TO BE AVOIDED: No decomposition if used according to specifications.
INCOMPATIBLE MATERIALS: No further relevant information available.
HAZARDOUS DECOMPOSITION PRODUCTS: Not anticipated under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS:

Acute Toxicity:

- LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimates)		
Oral	LD50	34014 mg/kg (rat)
Dermal	LD50	8362 mg/kg (rabbit)
Inhalative	LC50/4 h	1579 mg/l (rat)

- Primary irritant effect:**

On the skin:	Irritant to skin and mucous membranes
On the eye:	Irritating effect
Sensitization:	No sensitizing effects known

- Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant



Gulfcrown[®] EP Grease

SDS - Safety Data Sheet

- **Carcinogenic categories:**
 - IARC (International Agency for Research on Cancer)**
8052-42-4 Asphaltic Resin 2B
 - NTP (National Toxicology Program)**
None of the ingredients is listed.
 - OSHA-Ca (Occupational Safety & Health Administration)**
None of the ingredients is listed.

12. ECOLOGICAL INFORMATION

Avoid exposing to the environment, no specific aquatic data available.
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations.
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

14. TRANSPORTATION INFORMATION

Not regulated by DOT

15. REGULATORY INFORMATION

Safety, health and environment regulations/legislation specific for the substance or mixture

SARA

Section 355 (Extremely hazardous substances):

None of the ingredients is listed

Section 313 (Specific toxic chemical listings):

68457-79-4 Zinc Dialkylthiophosphate 0.1-<1%

TSCA (Toxic Substances Control Act):

All ingredients are listed.

Proposition 65:

Chemicals known to cause cancer:

None of the ingredients is listed.

Carcinogenic categories

EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV (Threshold Limit Value established by ACGIH)

8052-42-4 Asphaltic Resin A4

NIOSH-Ca (National Institute for Occupational Safety and Health)

8052-42-4 Asphaltic Resin

16. OTHER INFORMATION

The data in this Safety Data Sheet relates only to the specific material designated herein.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Nu-Tier Brands, Inc. The data on this sheet are related only to the specific material designated herein. Nu-Tier Brands, Inc. assumes no legal responsibility for use or reliance upon these data.

END OF SDS