



LUBRICANTS



Product Data Sheet

Gulfsol® 140

High purity paraffinic naphthenic solvent

High-purity mixture of hydrotreated isoparaffins and naphthenics with very low levels of polynuclear aromatics. It is a clear liquid with a minimum flash point specification of 142°F (Tag Closed Cup) and very mild odor.

Features and Benefits

- Mild low odor
- Minimum flash 142°

Applications

- Industrial and institutional cleaning
- Pesticide formulations, consumer products
- Oilfield drilling fluids, degreasers, lamp oil
- Paint and coatings, water treatment
- Lubricating oils, chemical process solvents
- Metal rolling oils, freeze point depressants

Typical Properties

Product Code	Test Method	380033
Distillation Range, °F		
IBP	ASTM D-86	350
10%		380
EP		430
Flash Point, °F (TCC)	ASTM D-56	>142
Pour Point, °F	ASTM D-97	<-94
Dry Point, °F	ASTM D-86	410
Specific Gravity, API, @ 60°F	ASTM D-4052	0.800 – 0.820
Appearance	Visual	Clear Liquid
Kauri-Butanol Value	ASTM D-1133	34
Aeromatics, %	ASTM D-3257	0.1
Color, Saybolt	ASTM D-156	+25
VOC Content, g/l	EPA Method 24	>700 g/l
Vapor Pressure, torr @ 20°C	API, calc	0.34
Avg Molecular Weight	API	156

*Note: Values shown are typical only and do not constitute a specification. Actual properties may vary from lot to lot.

Rev. 02/23



1-800-566-4853



East Greenbush, NY



www.nu-tierbrands.com

